

Relay Bridge Kit SFK-DS006-RELAY

Up to 1 mile range through obstructions and 50+ miles line-of-sight with patented Bunker Busting Technology. Using 900 MHz, works inside metal enclosures
Proprietary PCB Antenna design as well as FCC (USA) and IC (Canada) certified.



Specifications

Operating Voltage

12VDC +/- %5

Operating Current

0.08A (idle), 0.75A (transmit)

Operating Power

9 Watt (peak)

Transmit Power

1 Watt (30dBm)

Frequency Band

902 - 928Mhz

Channels

72 (Frequency Hopping)

Receiver Sensitivity

-133dBm

Link Budget

163dB

Range

Up to 1 mile through Obstructions. Greater than 40 Miles line-of-sight

Encryption Security

AES128

Battery Backup Connection

12V Sealed Lead Acid (SLA) type

Battery Charge Voltage

13.75V maximum at standby

Relays

2A 250VAC / 2A 250VDC Wet or Dry: NO, NC, COM

Operating Temperature

-40oC to +85oC (-40oF to +185oF)

Storage Temperature


-55oC to +125oC (-67oF to +257oF)

Mounting Options


DIN 35 (35mm x 7.5mm) or directly mount with two screws

Dimensions

Relay Controller Interface Front



Relay Remote Interface Front



Lifetime Warranty

Sure-Fi Inc | 116 E 800 S Smithfield, UT 84335

phone: +1-844-787-3340 | email: support@sure-fi.com | www.sure-fi.com