

Relay- Low Voltage Kit  
SFK-DS012-RELAY-LOW

Up to 1 mile range through obstructions and 50+ miles line-of-sight with patented Bunker Busting Technology. Using 900 MHz, works inside metal enclosures  
Proprietary PCB Antenna design as well as FCC (USA) and IC (Canada) certified.



**Specifications**

**Operating Voltage**  
24 VAC +/- %5

**Transmit Power**  
1 Watt (30dBm)

**Frequency Band**  
902 - 928Mhz

**Channels**  
72 (Frequency Hopping)

**Receiver Sensitivity**  
-133dBm

**Link Budget**  
163dB

**Range**

Up to 1 mile through Obstructions. Greater than 40 Miles line-of-sight

**Encryption**  
AES128

**Endpoint Relays**  
1A 60 V Peak NO, COM

**Operating Temperature**  
-40oC to +85oC (-40oF to +185oF)

**Storage Temperature**  
-55oC to +125oC (-67oF to +257oF)

**Dimensions**

Low Voltage Relay Endpoint Front



Low Voltage Relay Controller Front



Lifetime Warranty

Sure-Fi Inc | 116 E 800 S Smithfield, UT 84335

phone: +1-844-787-3340 | email: support@sure-fi.com | www.sure-fi.com